

DC Blocker

DCF 500/Set

Set of 2 pcs.



5 ... 2200 MHz



Model Art. No.	DCF 500/Set 871506
Impedance	75 Ω
Through loss trunk	Terr. SAT < 0,5 dB < 0,5 dB
Voltage max.	50 V
Dimensions	33 mm, 12 mm Ø


DC-Decoupled Terminating Resistor

ZFR 75 DC/Set

Set of 2 pcs.



5 ... 2200 MHz



Model Art. No.	ZFR 75 DC/Set 871511
Impedance	75 Ω
Voltage max.	30 V
Dimensions	27 mm, 12 mm Ø

DC-Decoupled Terminating Resistor

ZMR 75 DC/Set

Set of 2 pcs.



5 ... 2200 MHz



Model Art. No.	ZMR 75 DC/Set 871514
Impedance	75 Ω
Voltage max.	30 V
Dimensions	27 mm, 12 mm Ø

Push On 'F' male Coupler

ZSV 2 S/Set

Set of 5 pcs.



5 ... 2200 MHz



Model Art. No.	ZSV 2 S/Set 871508
Through loss trunk	Terr. SAT 0,2 dB 0,4 dB
Dimensions	29 mm, 12 mm Ø

RF Link Cables

ZVK 250 F/Set

Set of 5 pcs.



5 ... 2200 MHz



Model Art. No.	ZVK 250 F/Set 871505
Impedance	75 Ω
Through loss trunk	Terr. SAT 0,5 dB 1 dB
Dimensions	250 mm, 6 mm Ø

Ground Clamp:

EDKL 1/Set

- suitable for all F-sockets, especially for grounding UniSystem devices
- for equipotential bounding with 4 mm²

Set of 5 pcs.



Model Art. No.	EDKL 1/Set 872013
Dimensions (mm)	35 x 14,5 x 2